

Double Zaila (version 2) Kit with V-Mount Plates

Double Zaila Kit with V-Mount Plates

Reference: NZLK2E-D-V
EAN13: -



Includes 2x fixtures, 2x power supplies, 12x holographic film lenses, 8x hard gels, 2x lens pouches, 2x barn door sets, 2x gold mount battery adapters, and a Peli™ case w/insert

Caractéristiques :

Poids (kg): 2.3
Entrée AC: 100-240V
Consommation / Puissance (W): 45
Source: single-color, high brightness LEDs
IP: 50

DMX: 512 (RDM)
CRI/CQS: 90 (5600°K)
Température de couleur: 5600° K (daylight balanced)
Refroidissement: passif (sans ventilateur)
Dimmer: 0-100%
Angle beam: de 10° à 80°
Entrée DC: 10-18V
Température d'exploitation: -30-50°C
TLCI: 86 (5600°K)
Matériau: aluminum
Tension d'entrée: 0.4A at 100V AC
Vitesses d'obturation compatibles: all (flicker-free at any frame rate at 100% output, and up to 5000 fps when dimmed)
Durée de vie des LEDs: 20,000+ heures
Sortie UV: aucune
Spectre chromatique: continu
Méthode de mise au point: holographic film lenses
Connections de contrôle: RJ45 (adaptateur XLR 5 broches en option)
Chimera mount: intégré
certifications: ETL & CE
Fixation: yoke (w/junior pin and baby receiver)
operating position: any
Câble d'alimentation: 10' IEC (to external power supply)
Connecteur d'alimentation: NEMA 5-15P
Pays d'origine: USA