
Double Varsa (version 2) Kit with V-Mount Plates

Double Varsa (version 2) Kit with V-Mount Plates

Reference: NV2DBL-V
EAN13: -



Includes 2x fixtures, 12x holographic film lenses, 8x hard gels, 2x lens pouches, 2x barn door sets, 2x V-mount battery adapters, and a Peli Storm iM2950 case w/ custom foam insert

Caractéristiques :

Poids (kg): 5
Entrée AC: 100-240V
Consommation / Puissance (W): 75
Source: single-color, high brightness LEDs
IP: 65

DMX: 512 (RDM)
CRI/CQS: 90 (5600°K)
Température de couleur: 5600° K (daylight balanced)
Refroidissement: passif (sans ventilateur)
Dimmer: 0-100%
Angle beam: de 10° à 80°
Entrée DC: 10-18V
Température d'exploitation: -30-50°C
TLCI: 86 (5600°K)
Matériau: aluminum
Tension d'entrée: 0.65A at 115V AC
Vitesses d'obturation compatibles: all (flicker-free at any frame rate at 100% output, and up to 5000 fps when dimmed)
Durée de vie des LEDs: 20,000+ heures
Sortie UV: aucune
Spectre chromatique: continu
Méthode de mise au point: holographic film lenses
Connections de contrôle: RJ45 (adaptateur XLR 5 broches en option)
Chimera mount: intégré
certifications: ETL & CE
Fixation: yoke (w/junior pin and baby receiver)
operating position: any
Câble d'alimentation: 10' locking IP68 UTL
Connecteur d'alimentation: Souriau UTL (AC), 4-pin XLR (DC)
Pays d'origine: USA