



Combi Hoist

Connector Strip: up to 6 m (19'-8")

Lighting bar: up to 7.3 m (24')

Travel: up to 14 m (46')

Lighting circuits: up to 12

Cat 5: 1 / 2

Video and audio connections optional

Adjustable operating limits

Overload detection

Slack wire detection

Over travel limits

Thermal motor protection UL / CSA / CE /BGVC1

Reference: FF3907

EAN13: -



The Combi Hoist combines a simple design with the highest standards of construction and ease of installation for payloads up to 250kg.

The versatile Combi Hoist offers 2 key advantages; the lighting batten or rail can be customized between 3 to 7 meters in length and the ceiling mounting points can be adjusted to fit the studio structure. This versatility along with the price performance ratio for the hoist makes it a most valuable performer. The Combi Hoist employs one motor with dual cable lifting drums and two diverter pulleys. The hoist has 4 wire rope lifting cables and complies with the European safety regulations DIN 15560-46

The modular IFF Combi Hoist offers a wide range of design options for onstage electric hoists, front

EURO LIGHT System - 24, rue des Moulins - 95110 SANNOIS - FRANCE

Tel : +33 (0) 1.48.41.52.52 - Fax : +33 (0) 1.48.41.52.54

info@eurolight-system.com - www.eurolight-system.com

of house lighting hoists and scenery hoists. The drive unit and diverter pulley are mounted stationary to the ceiling. The moving section of the Combi Hoist is connector strip/lighting bar assembly. The complete system is under static and dynamic conditions self-sustaining, which makes susceptible mechanical braking systems mandatory and reduces the maintenance requirements to a minimum. The IFF radial winding drums eliminate any risk of cross winding during operation.

Caractéristiques :