



Combi Hoist

Connector Strip: up to 6 m (19'-8")

Lighting bar: up to 7.3 m (24')

Travel: up to 14 m (46')

Lighting circuits: up to 12

Cat 5: 1 / 2

Video and audio connections optional

Adjustable operating limits

Overload detection

Slack wire detection

Over travel limits

Thermal motor protection UL / CSA / CE /BGVC1

Reference: FF3907

EAN13: -



The Combi Hoist combines a simple design with the highest standards of construction and ease of installation for payloads up to 250kg.

The versatile Combi Hoist offers 2 key advantages; the lighting batten or rail can be customized between 3 to 7 meters in length and the ceiling mounting points can be adjusted to fit the studio structure. This versatility along with the price performance ratio for the hoist makes it a most valuable performer. The Combi Hoist employs one motor with dual cable lifting drums and two diverter pulleys. The hoist has 4 wire rope lifting cables and complies with the European safety regulations DIN 15560-46

The modular IFF Combi Hoist offers a wide range of design options for onstage electric hoists, front

of house lighting hoists and scenery hoists. The drive unit and diverter pulley are mounted stationary to the ceiling. The moving section of the Combi Hoist is connector strip/lighting bar assembly. The complete system is under static and dynamic conditions self-sustaining, which makes susceptible mechanical braking systems mandatory and reduces the maintenance requirements to a minimum. The IFF radial winding drums eliminate any risk of cross winding during operation.

Caractéristiques :