

Chargeur Numérique 4 voies Gold-Mount

Digital 4-Channel 3-Stud camera charger

Reference: XC-4LAD

EAN13: -



Fastest and most advanced charger offered in the PRO-X system line.

Front panel LCD is larger than the 2-channel model, making it easier to monitor all four batteries at the same time.

Multifunction LCD

PRO-X Digital chargers feature a large, backlit, multifunction LCD which displays charge status, battery type, serial number, charge current, chemistry, present temperature and voltage, charge/discharge cycle, battery capacity, and date of manufacture.

Battery Communication

PRO-X Digital chargers communicate with the batteries to acquire the real-time battery parameters. From the information received PRO-X Digital charger evaluates and selects the optimum charge program for the battery.

By tailoring the charge program to the battery, the charger insures maximum battery capacity and service life.

Quick charge current: 2 batteries (one on 1st or 2nd CH and another on 3rd or 4th CH) - 3A, 4 batteries - 2A

Power supply output: 70W/100W

Size: 12.5" x 2" x 10.2"

Weight: 5.5 lbs

Input voltage: 90-240V AC 50/60Hz

EURO LIGHT System - 24, rue des Moulins - 95110 SANNOIS - FRANCE

Tel : +33 (0) 1.48.41.52.52 - Fax : +33 (0) 1.48.41.52.54

info@eurolight-system.com - www.eurolight-system.com

Caractéristiques :

Consommation / Puissance (W): 70/100

Afficheur LCD: Display charge status, battery type, serial number, charge current, chemistry, present temperature and voltage, charge/discharge cycle, battery capacity, and date of manufacture

Monture: 3-Stud

Position de charge: 4 voies simultanées et rapide