
Déchargeur rapide 2 voies

2-Channel quick discharger

Reference: DXC-2LS

EAN13: -



DC-2LS/2LA features in integrating charge and discharge functions. The unit is able to charge 2 V Type/3-Stud batteries simultaneously. And it also can offer a very high discharge rate to be used for quick discharge in the situation where the battery remaining capacity is limited, such as air transport or deep discharge for battery's maintenance.

Charge

The battery can be charged fully rapidly via 3A(1-CH) or 1.5A(2-CH).

Quick Discharge

It takes about 40 minutes to discharge a 98Wh battery from 100% to 30%.

Battery maintenance

It takes about 55 minutes to discharge a 98Wh battery from 100% capacity to be empty.

Maximum Discharge Current: CH: 8A, CH-2: 4A

Low-voltage Protection

Stop discharging according to real-time capacity for digital battery.

Stop discharging at 13.5V(around 30%)/11V(0%) for non-digital battery.

Temperature Protection

The unit will stop discharging if the fan doesn't work.

LED indicator and should alarm.

Caractéristiques :

Protection: Low-Voltage protection, Temperature protection

Monture: V Type

Fonctions: 2-Channel Charge and quick Discharge, Battery maintenance

Indicateur: LED indicator and sound alarm.