



BaseLight 200W

BaseLight 200W, Bi-Color

Reference: PBL-200BIC

EAN13: -



ProFound Baselight is a superior uniformed light source suitable for a wide variety of scenes where color temperature, soft-lighting field and output are critical, with its versatile design and feature likes of adjustable CCT between 2800K and 6500K and continuous dimming from 0% to 100%.

Caractéristiques :

Poids (kg): 3,7 (w/o SMPS and barndoor)
Angle d'ouverture: 140°
Source: Ultra High CRI LEDx1782ea(200W)
Dimensions en mm: 526x391x101
CRI/CQS: jusqu'à 97
Température de couleur: 2800-6500K

EURO LIGHT System - 24, rue des Moulins - 95110 SANNOIS - FRANCE
Tel : +33 (0) 1.48.41.52.52 - Fax : +33 (0) 1.48.41.52.54
info@eurolight-system.com - www.eurolight-system.com

Alimentation: 100-240VAC 50/60Hz

Compatible RDM : DMX setup, hour counter and standard RDM commands

Dimmer: 0% à 100 %

TLCl: Typ.99

Lux: 5700lx at 1m (2800K) and 6400lx at 1m (6500K)

Batterie: batterie-saver : when the baselight is powered by a BP battery, its maximum output will be automatically adjusted to 170W to prevent overheating