

## Base light 200W BI-color



PF PBL200BIC

### Principales caractéristiques

Base light 200W BI-color. (Ref : PF PBL200BIC.)

ProFound Baselight is a superior uniformed light source suitable for a wide variety of scenes where color temperature, soft-lighting field and output are critical, with its versatile design and feature likes of adjustable CCT between 2800K and 6500K and continuous dimming from 0% to 100%.

#### Caractéristiques

Poids (kg) : 3,7 (w/o SMPS and barndoor)

Angle d'ouverture : 140°

Source : Ultra High CRI LEDx1782ea(200W)

Dimensions en mm : 526x391x101

CRI/CQS : jusqu'à 97

Température de couleur : 2800-6500K

Alimentation : 100-240VAC 50/60Hz

Compatible RDM : DMX setup, hour counter and standard RDM commands

Dimmer : 0% à 100 %

TLCl : Typ.99

Lux : 5700lx at 1m (2800K) and 6400lx at 1m (6500K)

Batterie : batterie-saver : when the baselight is powered by a BP battery, its maximum



output will be automatically adjusted to 170W to prevent overheating

**Spécifications techniques****Valeur de la spécification**

Capteur LED	CCT
Puissance	200W
Plage CCT	2 800 K - 6 500 K
TLCI	99
IRC	98
DMX	Bluetooth, CRMX, DMX512, RDM
Indice IP	54

